



Providing Access Control Solutions since 1979

o p e n | m o d u l a r | s c a l a b l e | i n t u i t i v e

## New Product Release

***Sielox is pleased to announce  
that our newest Controller, the 1500 Series, is now shipping!***

### Sielox 1500 Controller Series

The Sielox 1500 Controller manages from 2 doors up to 16 doors in the large configuration or from 2 doors up to 4 doors with the small configuration.

It includes a built in power regulator/UPS/Battery charger module that keeps the controller working in the event of a power failure.

Communication options include Ethernet (LANLink™ 1500) or RS-485 (AC-1500).

When used in conjunction with the X-LAN, up to 32 doors can be managed with a single Ethernet connection.

- 2 doors, 2 request to exit, 2 door contacts and door locks
- 50,000 card holder database
- 10,000 off-line events
- 256 access levels
- 64 time zones
- 4 general purpose inputs (supervised or unsupervised)
- 4 general purpose outputs
- I / O Expansion
- Real Time Clock (RTC)
- Battery Charger with Main Power Loss Signal
- Lithium battery backup keeps the cardholder database, off-line events and RTC running in case of power loss
- Status lights for lithium battery, communications and power
- LAN or RS-485
- Certifications: FCC part 15, ETL Certified to UL 294 and UL 1076

For more information contact your regional sales manager or click on the links below:

[1500 Datasheet](#)

[X-LAN Datasheet](#)

[www.sielox.com](http://www.sielox.com)